

Low Level Carbon Monoxide Monitor

True Protection For All Ages

Your family needs the added CO sensitivity required for infants, children, elderly and highly sensitive or ill people.

The NSI 3000 lets you know there is a problem before reaching dangerous levels and long before other Carbon Monoxide detectors begin to work.



The NSI 3000 Offers Real Protection

- Continuous Scan[™] mode lets you know monitor is checking for CO 24/7
- Digital display shows CO levels of 5ppm or higher
- Low Alarm 15 ppm audible & visual every 8 seconds
- High Alarm 35 ppm audible & visual every 4 seconds
- Crisis Alarm -70+ ppm -audible & visual every 2 seconds
- 5-minute "Hush" button for levels below 70 ppm
- Designed for wall installation or tabletop use
- Replaceable 9V battery ensures operation even when power is out
- 2-Year limited Warranty

Don't forget to combine your NSI 3000 Professional Grade Carbon Monoxide Monitor with a complete home CO checkup

Contact Your Local NCI Certified Contractor



NCL 859.525.0100 A&B Heating and Air

ABHVAC.COM

Carbon Monoxide **A B O**

Why do I need a low-level monitor?

The NSI low level monitor senses CO levels as low as 5 ppm (parts per million). Infants, children, elderly, persons with respiratory or heart ailments are provided little or no protection from deadly CO with standard alarms. Long term exposure to Low-level CO above 15 ppm can cause illness and even permanent disabilities.

What about other "detectors" sold at retailers and home centers?

Store-bought detectors don't alarm until unsafe levels of 70 ppm or higher are present at the unit for 3-1/2 hours! By then it may be too late. Plug-in models don't always allow for proper placement and don't work during power outages. The NSI 3000 is battery powered for 24/7 protection.

Why is the NSI 3000 more expensive than the others?

Accurate, low-level CO detection requires more expensive components & quality control. The NSI 3000 CO monitor uses the same technology and sensors as in professional-grade CO analyzers used by contractors, fire departments, and utilities. And NSI's unique Continuous Scan mode lets you know the monitor is operational 24/7!

Where should I place the NSI 3000

CO is lighter than air. Monitors should be mounted at eve level and no lower. They should be placed in an area with good air circulation. If you have only one monitor it should be placed near the master bedroom. Additional locations include your kitchen, nursery, basement, rooms with fireplaces or gas logs, and near your heating system and/or hot water tank. Your professional installation contractor will determine the best location in your home.

What if my NSI monitor goes off?

Call your CO-Certified contractor at any level below 70 ppm, unless you have symptoms. CO exposure can cause nausea, severe headache, shortness of breath, chest pain, blurred vision, and dizziness. If you experience these symptoms call 911 and leave the house immediately. Above 70ppm, evacuate immediately. If you have symptoms, call 911 from a neighbors house. Call your utility to turn off the equipment until your CO-Certified contractor can investigate the source of carbon monoxide.

